

Safety Data Sheet



SECTION 1: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Manufacturer's Name Fox Blocks – Airlite Plastics
6110 Abbott Drive
Omaha, NE 68110

Emergency Telephone 877-369-2562

SDS Competent Person info@foxblocks.com

Date Prepared June 3, 2016
Revisions Date June 9, 2016
Product Name Fox Blocks
Formula Substance
Product Use For use as a stay-in-place formwork for a cast-in-place concrete wall used in residential and commercial exterior and interior walls.

SECTION 2: HAZARDS IDENTIFICATION

GHS Hazard Class Not applicable. This product does not meet the physical, health or environmental classification criteria of GHS (Globally Harmonized System).
Hazards not otherwise classified (HNOC) – None

Hazard Classification Not classified as hazardous based on IATA, IMDG, and DOT.

Fire and Explosion Not considered flammable or combustible, but this product will burn if involved in a fire.

Potential Health Effects <0% of mixture consists of ingredients of unknown acute toxicity.

Appearance White EPS foam and black plastic ties.

NFPA Rating

COMPONENT	HEALTH (BLUE)	FLAMMABILITY (RED)	REACTIVITY (YELLOW)	SPECIAL (WHITE)
Fox Blocks	1	2	0	-

Safety Data Sheet



TECHNICAL BULLETIN . SPECIFICATIONS & STANDARDS

1.04.05

SECTION 3: COMPOSITION, INFORMATION ON INGREDIENTS

PRODUCT COMPOSITION	APPROX %	CAS NUMBER	EC NUMBER	CANADA DSL
EPS RESIN				
Expanded Polystyrene (EPS)	> 95	9003-53-6	500-008-9	Y
Pentanes	< 1	109-66-0	203-692-4	Y
Flame Retardant	< 1	TS	TS	Y
Coatings	< 1	-	-	N
PP RESIN				
Recycled Polypropylene	> 95	9010-79-1	-	Y
Stabilizers and Additives	< 5	Mixture	-	N

Some items on this SDS may be designated as trade secrets (TS). Bonafide requests for disclosure of trade secret information to medical personnel must be made in accordance with the provisions contained in 29 CFR 1910.1200 I 1-13.

SECTION 4: FIRST AID MEASURES

Description of First Aid Measures

- Inhalation** Remove to fresh air. If not breathing, provide CPR (Cardio Pulmonary Resuscitation). Get immediate medical attention.
- Skin Contact** Wash skin with plenty of soap and water. If hot material gets on skin, immediately flush affected area with large amounts of cool water. Do not attempt to remove the material from the skin, or to remove contaminated clothing. Get immediate medical attention.
- Eye Contact** Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses if present and safe to do so. If hot material comes in contact with eyes hold the eyelids apart and flush the eye with a large amount of cool water for at least 15 minutes. Get immediate medical attention.
- Ingestion** If swallowed do NOT induce vomiting, rinse mouth with water. Never give anything to an unconscious person. Get immediate medical attention.

Most Important Symptoms and Effects, Both Acute and Delayed

- Symptoms/Injuries After Inhalation** Dust and/or vapors may cause respiratory tract irritation. In confined or poorly ventilated areas, vapors can readily accumulate and can cause unconsciousness and death.

Safety Data Sheet



TECHNICAL BULLETIN . SPECIFICATIONS & STANDARDS

1.04.05

Symptoms/Injuries After Skin Contact May cause skin irritation. Symptoms may include redness, drying, defatting, and cracking of the skin.

Symptoms/Injuries After Eye Contact May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.

Symptoms/Injuries After Ingestion May be harmful if swallowed. May cause stomach distress, nausea, or vomiting.

Indication of any Immediate Medical Attention and Special Treatment Needed

Inhalation: This material (or a component) sensitizes the myocardium to the effects of sympathomimetic amines. Epinephrine and other sympathomimetic drugs may initiate cardiac arrhythmias in individuals exposed to this material. Administration of sympathomimetic drugs should be avoided.

Eyes: Hot material may cause burns to the eyes. Early ophthalmologic evaluation is recommended.

Skin: Hot material may cause skin burns. Immerse skin covered with hot material in cool water to limit tissue damage and prevent spread of liquid material.

Symptoms may not appear immediately. In case of accident or if you feel unwell, seek medical advice immediately.

SECTION 5: FIRE-FIGHTING MEASURES

Suitable Extinguishing Media Use foam, dry chemical, or carbon dioxide. Do not use solid water stream as it may scatter and spread fire.

Special Hazards Arising from the Substance or Mixture Combustion may produce hazardous decomposition products and other decomposition products in the case of incomplete combustion. These may include simple hydrocarbons to toxic and irritating gases such as carbon, carbon monoxide, carbon dioxide, styrene, acids, ketones, and aldehydes. Material is a solid containing an extremely flammable liquid and vapor. Material will burn on contact with flame or exposure to high temperature. Hazardous melting and dropping may occur at elevated temperatures. Explosion hazard if exposed to extreme heat. This material releases a flammable blowing agent. Extremely flammable vapors form flammable or explosive mixtures with air at room temperature. Vapor or gas may spread to distant ignition sources and flash back. Eliminate ignition sources (including static spark) and prevent vapor accumulation. This material, as produced and not in its finely divided form as dust, is not explosive as defined by established regulatory criteria. When in its finely divided form as dust, this material presents an explosion hazard when dispersed in a confined area and ignited in air. Risk of dust-air explosion is increased if flammable vapors are present. This material may accumulate static charge which can cause an electrical spark (ignition source) in some cases. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material.

Safety Data Sheet



TECHNICAL BULLETIN . SPECIFICATIONS & STANDARDS

1.04.05

Protective Actions Fire-Fighters Wear standard protective equipment and self contained breathing apparatus for firefighting if necessary.

Further Information Use water spray to cool unopened containers.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and Emergency Procedures

Wear proper personal protective equipment. Avoid breathing dust, fine particulate, vapors and/or mist.

Environmental Precautions

Prevent further leakage or spillage if safe to do so. Prevent spills or contaminated rinse water from entering sewers or watercourses.

Methods and Materials for Containment and Cleaning Up

For Small Spill: In the event of a small spill, clean up area with non-sparking tools and place into an appropriate container for disposal. Avoid the generation of dust clouds and contamination of waterways.

For Large Spill: In the event of a large spill, keep unnecessary people away. Isolate area for at least 25 meters (75 feet) in all directions to preserve public safety. If downwind consider initial evacuation for at least 100 meters (300 feet). Eliminate all sources of ignition (no smoking, flares, sparks or flames in immediate area). Prevent or minimize formation of a dust cloud or layer during cleanup. This material releases a flammable blowing agent. In its finely divided form, this material may present an explosion hazard when dispersed in a confined area and ignited in air.

Water Spill: Use appropriate containment to avoid run off or release to sewer or other waterways.

Land Spill: Use appropriate containment to avoid run off or release to ground.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Take precautionary measures against static discharge.

Keep away from heat, sparks, flame, direct sunlight, and other possible sources of ignition.

Use only with adequate ventilation.

Do not inhale dust or vapors.

Avoid spilling and releasing dust and vapor.

Wear proper protective equipment when handling this material.

Avoid contact with skin, eyes, or clothing.

Wash hands after handling this material.

Appropriate container should be used for disposal.

For precautions see Section 2.

Safety Data Sheet



Conditions for Safe Storage, Including any Incompatibilities

- Store upright in a cool, dry place.
- Keep container closed when not in use.
- Prevent build-up of electro-static charges (e.g. by grounding).
- Keep away from heat, sparks, flame, direct sunlight, and other possible sources of ignition.
- Do not store with acid, metallic oxide, amines, and combustible materials.
- Utilize chemical segregation.
- Follow all applicable local regulations for handling and storage.

Specific Uses

This product is intended for use as a stay-in-place formwork for a cast-in-place concrete wall used in residential and commercial exterior and interior walls.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

PRODUCT COMPOSITION	ACGIH TLV	OSHA PEL	NIOSH REL
EPS RESIN			
Expanded Polystyrene (EPS)	TWA 3 mg/m ^{3**} 10 mg/m ^{3**}	TWA 5 mg/m ^{3**} 15 mg/m ^{3**}	TWA 3 mg/m ^{3**} 10 mg/m ^{3**}
Pentanes	TWA 120 ppm (350 mg/m ³)	TWA 1000 ppm (2950 mg/m ³)	TWA 120 ppm (350 mg/m ³) C 610 ppm (1800 mg/m ³) [15-minute]
Coatings	-	-	-
PP RESIN			
Recycled Polypropylene	-	-	-
Stabilizers and Additives	-	-	-

* PNOR (Particulates Not Otherwise Regulated): OSHA 5 mg/m³ Respirable Fraction (R), 15 mg/m³ Total Particulates

** PNOS (Particulates Not Otherwise Specified): ACGIH 3 mg/m³ Respirable Fraction (R), 10 mg/m³ Total Particulates, total dust less than 1% quartz.

Exposure Controls

Ventilation

Always provide good general, mechanical room ventilation where this chemical/material is used.

Special Ventilation Controls

Use explosion-proof equipment if high dust/air concentrations are possible. Use only appropriately classified electrical equipment and powered industrial trucks. If user operations generate dust, fume or mist,

Safety Data Sheet



use ventilation to keep exposure to airborne contaminants below the exposure limit. It is recommended that all dust control equipment such as local exhaust ventilation and material transport systems involved in handling of this product contain explosion relief vents, an explosion suppression system or an oxygen deficient environment. Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust in to the work area (i.e. there is no leakage from the equipment).

Respiratory Protection

Follow the OSHA respirator regulations found in 29 CFR 1910.134 or the CEN European Standards (EU). Use a NIOSH/MSHA or European Standard (EN) approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Protective Gloves

Neoprene, butyl, or nitrile rubber glove are recommended.

Eye Protection

Recommend eye protection using safety glasses or goggles.

Skin Protection

Suitable protective clothing to prevent skin contact.

Work/Hygiene Practices

Avoid breathing dust or vapor. Avoid contact with eyes. Wash hands after handling.

Other Equipment

Make safety shower, eyewash stations, and hand washing equipment available in the work area.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

	PRODUCT CRITERIA - EPS	PRODUCT CRITERIA - PP
Appearance - Color	White or Grey	Charcoal to Black
Physical State	Solid	Solid
Odor	Very Slight Hydrocarbon Odor	Mild to Odorless
Odor Threshold	Data Not Available	Data Not Available
PH	Data Not Available	Data Not Available
Melting Point / Freezing Point	70°C (160°F)	90°C (200°F)
Initial Boiling Point and Boiling Range	Data Not Available	Data Not Available
Flash Point	400°C (752°F)	Data Not Available
Evaporation Rate	Data Not Available	Data Not Available
Flammability (Solid, Gas)	Data Not Available	Data Not Available
Upper/Lower Flammability or Explosive Limits	Data Not Available	Data Not Available

Safety Data Sheet



TECHNICAL BULLETIN . SPECIFICATIONS & STANDARDS

1.04.05

	PRODUCT CRITERIA - EPS	PRODUCT CRITERIA - PP
Vapor Pressure	Data Not Available	Data Not Available
Vapor Density (Air = 1)	Data Not Available	Data Not Available
Specific Gravity (H2O = 1)	0.60 - 2.0 (Estimated)	0.85 - 0.1 (Estimated)
Density (@25°C)	1.35 - 1.65 lbs/cubic feet	1.02 g/ml
Solubility (IES)	Insoluble	Insoluble
Oxidizing Properties	Data Not Available	Data Not Available
Partition Coefficient: n-octanol/water	Data Not Available	Data Not Available
Auto Ignition Temperature	380°C (716°F)	Data Not Available
Decomposition Temperature	Data Not Available	Data Not Available
Viscosity	Data Not Available	Data Not Available
Explosive Properties	Data Not Available	Data Not Available

SECTION 10: STABILITY AND REACTIVITY

Reactivity	Not Reactive
Chemical Stability	Stable under normal conditions.
Possibility of Hazardous Reactions	Will not occur under normal temperatures and pressures.
Conditions to Avoid	Unventilated areas, heat, open flame, sparks and ungrounded electrical equipment.
Incompatibility (Materials to Avoid)	Solvents including hydrocarbons, esters, aldehydes, and amines. Also avoid strong oxidizers.
Hazardous Decomposition Products	Decomposition of the product can include trace amounts of hydrocarbons. Primary combustion products include carbon monoxide, carbon dioxide, styrene, hydrogen halide, nuisance particulate, carbon (soot) and pentanes.

Safety Data Sheet



TECHNICAL BULLETIN . SPECIFICATIONS & STANDARDS

1.04.05

SECTION 11: TOXICOLOGICAL INFORMATION

There is no toxicological information available for the product.

GHS REQUIRED CRITERIA	TOXICITY CRITERIA	TOXICITY INFORMATION	COMMENTS	CHEMICAL CONSTITUENT
Acute Toxicity	LD50 (Oral/Rat)	2,000 mg/kg	No mortality	Pentane
	LC50 (Inhalation/Rat)	205.45 mg/L, 4hr		Pentane
Skin Corrosion/Irritation	There was no stimulativeness to the human skin by the 24-hour patch test in the humans and there was no stimulativeness in practice by the skin irritation study in a rabbit (the erythema and dropsy with the average values of Draize score of 0.67).			Pentane
Serious Eye Damage/ Eye Irritation	EYE-RABBIT:	Transient conjunctivitis was seen, however, it recovered within 72 hours.	Category 2B	Pentane
Respiratory or Skin Sensitization	No sensitizing properties seen in the Maximization Test using the guinea pigs.			Pentane
Germ Cell Mutagenicity	Negative micronucleus tests using rat myeloid cells of in vivo.			Pentane
Carcinogenicity	NTP	Not Listed		
	IARC	Group 3		Polystyrene
	OSHA	Not Listed		
Reproductive Toxicity	There is a description that no influence on dam and fetus was observed in the teratogenicity test by oral administration using rats, even at the highest dose of 1000mg/kg/day.			Pentane
STOT* - Single Exposure	There were anesthetic actions and respiratory irritant through inhalation exposure to laboratory animals.		Category 3	Pentane
STOT* - Repeated Exposure		Data Not Available		
Aspiration Hazard		Data Not Available		

* STOT = Specific Target Organ Toxicity

Safety Data Sheet



SECTION 12: ECOLOGICAL INFORMATION

		CHEMICAL CONSTITUENT
Toxicity	48-Hour EC50 = 2.7mg/L, Crustacea (Daphnia magna)	Pentane
Persistence and Degradability	Data Not Available	
Bioaccumulative Potential	Data Not Available	
Mobility in Soil	Data Not Available	
PBT and vPvB Assessment	PBT/vPvB assessment not available as chemical assessment not required /not conducted.	
Other Adverse Effects	Data Not Available	

SECTION 13: DISPOSAL CONSIDERATIONS

Waste from Residue/ Unused Products

Follow the waste disposal requirements of your country, state, or local authorities.

Contaminated Packaging

Contaminated packaging material should be disposed of as stated above for residues and unused product.

Rinsate

Do not dispose of rinse water containing product in a sanitary sewer system or stormwater drainage system.

SECTION 14: TRANSPORT INFORMATION

DOT Transport

Not Regulated

ADR = International Carriage of Dangerous Goods by Road Not Regulated

Sea Transport

IMDG

Not Regulated

Air Transport

IATA/ICAO

Not Regulated

SECTION 15: REGULATORY INFORMATION

Toxic Substance Control Act (TSCA) Status

This product is in compliance with rules, regulations, and orders of TSCA. All components are either listed on a federal chemical inventory or are considered exempt.

Superfund Amendments and Reauthorization Act of 1986 (SARA) Title III Section 313 Supplier Notification

This regulation requires submission of annual reports of toxic chemical(s) that appear in Section 313 of the Emergency Planning and Community Right To Know Act of 1986 and 40 CFR 372. This information must be included in all SDSs that are copied and distributed for the material.

Safety Data Sheet



California Proposition 65

This regulation requires a warning for California Proposition 65 chemical(s) under the statute.

The California proposition 65 chemical(s) contained in the product are: This material may contain low levels of Styrene and Ethyl Benzene with exposure of no significant risk.

State Right-To-Know Toxic Substance or Hazardous Substance List

Massachusetts Hazardous Substance(s):	Pentane
Pennsylvania Hazardous Substance(s):	Pentane
New Jersey:	Pentane

Canada

WHMIS-2015 This SDS is in compliance with WHMIS 2015 (HPR/new HPA).

European Union

This product has been reviewed for compliance with the following European Community Directives: REACH 1907/2006; Regulation (EC) No 1272/2008 on classification, labeling, and packaging (CLP) of substances and mixtures.

SECTION 16: OTHER INFORMATION

Initial Issue Date	June 3, 2016
Final Revision Date	June 9, 2016
Revision Number	0
Revision Explanation	Initial Version
Information Sources	RTECS, ECHA, REACH, OSHA 29 CFR 1910.1200

Disclaimer

"This document is generated to distribute health, safety and environmental data. It is not a specification sheet and none of the displayed data should be construed as a specification. Information on this SDS sheet was obtained from sources which we believe are reliable, and we believe that the information is complete and accurate. However, the information is provided without any warranty, express or implied, regarding its correctness. Some of the information presented and conclusions drawn are from sources other than direct test data of the substance. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may also be beyond our knowledge. It is the user's responsibility to determine the suitability of any material for a specific purpose and to adopt such safety precautions as may be necessary. If the product is used as a component in another product, this SDS information may not be applicable. For these reasons, we do not assume any responsibility and expressly disclaim liability for any loss, damage or expense arising out of or in any way connected with handling, storage, use or disposal of this product."

This SDS complies with GHS Revision 5, OSHA 29CFR 1910.1200

SDS AUTHORED BY

Aegis Environmental Strategies
Safety and Environmental Compliance

WWW.AEGIS-EHS.COM